



EVO-STIK Decorators Flexible Filler

HIGH QUALITY ACRYLIC DISPERSION SEALANT

Date: 22 June 2016

Fact Sheet No.:

YOUR SMART ADVANTAGES

- High quality acrylic dispersion sealant, interior use
- Easy to apply, Easy to clean , almost odourless
- Paintable with water based and synthetic paint

USES

EVO-STIK Decorators Flexible Filler is a plasto elastic sealant based on an acrylic emulsion. After application the product forms a tough plastic elastic rubber by evaporation of water from the sealant. It has been especially developed for sealing connection joints between stairs, walls, ceilings, skirting boards, windowsills, wooden and metal window frames, concrete and brickwork for interior applications. It is paintable with water based and synthetic paints. Perfect adhesion without primer on most, even slightly damp substrates. Easy to apply. Easy to clean. Non corrosive towards metals.

NOTE : Not suitable for continuous exposure to water. Not suitable for PE,PP,PC,PMMA, neoprene and bituminous substrates.

PRODUCT CHARACTERISTICS

Colour	White
Form	Acrylic Sealant
Specific Gravity	
Composition	Acrylic dispersion sealant
Product Code	30810636 White 300ml x 12
Storage/Shelf Life	In unopened original packaging between -5C and +25C, shelf life 18 months. Store in dry conditions.

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	+5°C to +30°C
Service Temperature	-20°C to +75°C
Coverage	Approx : 10 metres of 5mm diameter bead per cartridge
Drying Times	Skin formation 7 mins @ 23C/55%RH
Solvent for Cleaning Up	Tools can be cleaned after use with water. Hands can be cleaned with water and soap.

DIRECTIONS FOR USE

IMPORTANT: Before using EVO-STIK Decorators Flexible Filler refer to the relevant Health & Safety Data Sheet, available at www.bostik.ie.

PREPARATION

1. Surfaces must be sound, clean and free from contaminants such as dust, oil, grease and any loose material. Substrate to be cleaned from all loose particles, porous substrate do not require to be absolutely dry. Very porous substrates such as : Gypsum, airated concrete, limestone, etc. need to be primed. Adhesion tests prior to application are recommended. Finish and smoothen with water.
2. Cut off the dome at the top of the cartridge taking care not to damage the thread. Cut the nozzle at a 45° angle to the required diameter and screw onto the cartridge.
3. Insert the cartridge into a cartridge gun and repeatedly squeeze the trigger until the adhesive appears.

APPLICATION

4. Application temperature +5C to +30C.



FM 01696
BS EN ISO 9001:2008

Bostik Industries Ltd. Newtown, Swords, Co. Dublin, Ireland. Tel: +353 1 8624900 www.bostik.ie

5. The product is paintable after full drying of sealant. During curing product will show shrinkage, which can cause cracking of the paint. Recommended to test compatibility with paint prior to application.
6. Beads 5mm in diameter are generally sufficient.

CLEANING

7. Tools to be cleaned after use with water. Hands can be cleaned with water and soap.

PRECAUTIONS IN USE

For any application not covered please contact Technical Services on +353 1 8624998 or visit www.bostik.ie for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for EVO-STIK Decorators Flexible Filler, available at www.bostik.ie.



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 01 8624999	Fax: 01 8402186	orders.bostik-irl@bostik.com
Technical Advice	Tel: 01 8624998	Fax: 01 8402186	
Technical Data & COSHH (MSDS) Data Sheets	Tel: 01 8624900	Fax: 01 8402186	



FM 01696
BS EN ISO 9001:2008

Bostik Industries Ltd. Newtown, Swords, Co. Dublin. Ireland. Tel: +353 1 8624900 www.bostik.ie



DECLARATION OF PERFORMANCE

In accordance with Annex III of Regulation (EU) No 305/2011
(Construction Products Regulation)

Product Description: **Bostik Evostik Decorators Filler 300ml**

Product Barcode(s):

Intended Use: **Sealant for façade for interior application.**

Manufacturer: **Bostik Ireland Limited**

Contact Address: **Newtown,
Swords,
Co. Dublin**

System of Assessment: **System 4**

Harmonised Standard: **ENT15651-1: F-INT**

Notified Body: **1213**

Essential Characteristics	Performance	Harmonised technical specification
Reaction to Fire	F	BS EN 15651-1:2012
Release of Chemicals	None	See Safety Data Sheet
Water Tightness & Air Tightness as determined by:		
Resistance to Flow	<5 mm	BS EN 15651-1:2012
Loss of Volume	<45%	
Elongation At Break(ISO 8839)	>25%	
Durability	NPD	

This declaration of performance is issued under the sole responsibility of Bostik Ireland Ltd.

Signed for and on behalf of Bostik Ireland Ltd by:-

Name : **Brian Monaghan**

Signature:

Date: June 2016