



EVO-STIK EXPANDING FOAM

HAND HELD

Date: 04 July 2016

Fact Sheet No.:

YOUR SMART ADVANTAGES

- Excellent adhesion to concrete, plaster, brick works, wood and many plastic materials
- Excellent muffling and insulating qualities
- High Quality PU Foam

USES

EVO-STIK EXPANDING FOAM is a one component polyurethane foam curing by air moisture, applicable with annexed straw. It expands rapidly to fill and seal holes around window and door frames, or in brickwork, rendering and plaster - then hardens ready to be trimmed, cut, sanded and painted.

PRODUCT CHARACTERISTICS

| | |
|--------------------|--|
| Colour | Straw colour - Light Yellow |
| Form | Aerosol Foam |
| Raw Density | Free Foamed - Appr. 20-30Kg.m3 |
| Composition | Polyurethane |
| Product Code | 30810641 500ml x 12 30810642 750ml x 12 |
| Storage/Shelf Life | Always store upright in cool, dry conditions between +5oC and 25oC. 18 months. Store Valve up. |

TYPICAL PERFORMANCE DATA (Approx.)

| | |
|-------------------------|-------------------------------|
| Application Temperature | +5°C to +30°C / optimum +20°C |
|-------------------------|-------------------------------|

| | |
|-------------------------------|--|
| Temp. resistance after curing | -40°C to +90°C |
| Fire behaviour | B3 |
| Drying Times | Cured after approx. 50 to 150 mins. |
| Solvent for Cleaning Up | EVO- STIK Foam Cleaner for uncured foam and Mechanical for cured foam. |

DIRECTIONS FOR USE

IMPORTANT: Before using EVO-STIK EXPANDING FOAM refer to the relevant Health & Safety Data Sheet, available on www.bostik.ie.

PREPARATION

1. Surfaces must be sound, stable, clean and free from contaminants such as dust, oil, grease and any loose material. Moisten surfaces. Gypsum and porous surfaces shall be pre treated with primer. Wear protection glasses and gloves, hold ready foam cleaner.
2. Screw adaptor into can. Shake well.
3. Press lever carefully to regulate extrusion rate.

APPLICATION

4. Vertical gaps and cavities have to be filled from bottom up. Do not overfill. Wide gaps shall be filled with several layers. (wait 15-30 minutes between applications) Moisture before each application. If applying outdoors, protect foam by painting or coating with suitable material. Foaming at constructional elements requiring advanced fire security standards. Ideal construction and insulation foam for filling and sealing of cavities between brick work and window frames, window sills, roller blinds chassis etc. Insulating of pipeline mountings. Not suitable for applications under water.
5. After ending work, flush the adaptor and clean valve.



FM 01696
BS EN ISO 9001:2008

Bostik Industries Ltd. Newtown, Swords, Co. Dublin, Ireland. Tel: +353 1 8624900 www.bostik.ie

CLEANING

6. Uncured product may be removed using EVO-STIK Foam Cleaner..
7. Cured product can only be removed by mechanical means.

PRECAUTIONS IN USE

For any application not covered please contact Technical Services on +353 1 8624998 or visit www.bostik.ie for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for EVO-STIK EXPANDING FOAM , available at www.bostik.ie.

BOSTIK HOTLINE

Smart help +353 1 8624998



FM 01696
BS EN ISO 9001:2008

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

| | | | |
|---|-----------------|-----------------|--|
| Sales | Tel: 01 8624999 | Fax: 01 8402186 | orders.bostik-irl@bostik.com |
| Technical Advice | Tel: 01 8624998 | Fax: 01 8402186 | |
| Technical Data & COSHH (MSDS) Data Sheets | Tel: 01 8624900 | Fax: 01 8402186 | |



FM 01696
BS EN ISO 9001:2008

Bostik Industries Ltd. Newtown, Swords, Co. Dublin. Ireland. Tel: +353 1 8624900 www.bostik.ie